

Chemicals contained in products

Package-type

Epson Package name; **PFBGA8U-121 / Mold : Halogen free**

JEITA Package name; **(P-TFBGA-121-0808-0.65)**

Solder ball Type; **Lead(Pb) Free**

Weight; **0.13 [g]** *Note1

Part	Subpart	Subpart weight [mg]	Substance name	CAS No.	Content ※2		Application		
					[mg]	[ppm]			
IC Die	IC Die	14	Silicon	7440-21-3	13.7	999894	Base material		
			Boron	7440-42-8	0.00003	2	Dopant		
			Phosphorus	7723-14-0	0.00007	5	Dopant		
			Aluminum	7429-90-5	0.0003	20	Metalization		
			Arsenic *Note3	7440-38-2	0.00007	5	Dopant		
			Fluorine *Note3	7782-41-4	0.00003	2	Dopant		
			Titanium *Note3	7440-32-6	0.0003	20	Metalization		
			Molybdenum *Note3	7439-98-7	0.0003	20	Metalization		
			Tungsten *Note3	7440-33-7	0.0004	30	Metalization		
			Cobalt *Note3	7440-48-4	0.00003	2	Metalization		
Package	Stress buffer coat	0.27	Polyimide	-	0.27	1000000	Stress buffer coat *Note4		
	Substrate	27	Glass-cloth	-	1.4	52140	Reinforcement		
			Silica	-	0.70	26180	Filler		
			Halogenated compound(Brominations epoxy)	-	2.2	81400	Flame retardant		
			Epoxy resin	-	2.3	86280	Base material		
			Acrylate resin	-	1.5	54600	Base material		
			Pigment	-	1.3	46800	Additive		
			Organic filler	-	0.070	2600	Filler		
			Arsenic	7440-38-2	0.0007	26	Burning resistance		
			Chromium compound	-	0.0005	20	Burning resistance		
			Copper	7440-50-8	16.9	629154	Copper foil		
			Nickel	7440-02-0	0.45	16900	Plating		
			Gold	7440-57-5	0.10	3900	Plating		
			Die Bonding material	1.9	Epoxy resin	-	1.3	670000	Adhesive
					Acrylic resin	-	0.63	330000	Adhesive
	Solder ball	10	Tin	7440-31-5	10.0	957500	Solder ball		
			Silver	7440-22-4	0.36	35000	Solder ball		
			Copper	7440-50-8	0.078	7500	Solder ball		
	Bonding Wire	2.2	Gold	-	2.2	1000000	Conductor		
	Mold resin	75	Epoxy resin	-	3.7	50000	Base material		
			Silica	60676-86-0/-	65.2	873000	Filler		
			Carbon black	1333-86-4	0.15	2000	Coloring agent		
			Hardening chemical(ex:Phenol resin)	-	3.7	50000	Base material		
			Organic phosphorous compound	-	0.37	5000	Hardening accelerator		
			others	-	1.5	20000	Additive		

Regarding the information of chemical substances

*Note1 The weight might be somewhat different depending on an individual built-in IC-chip specification like the size etc.

*Note2 Content data are estimated values based on supplier information and intended levels of content in product.

Actual measurements may vary from these values somewhat.

*Note3 Use or not-use of these substances depends on individual built-in IC-chip specification.

*Note4 The stress buffer coat may not be used depending on the individual model.