

Low Power 16-bit Single Chip Microcontroller

- Low Power MCU (Operating voltage 1.8V, 1.2uA/ SLEEP, 2.7uA/ HALT)
- 128K-Byte Flash Memory, 12KB RAM
- High quality, stable display LCD driver (72SEG x 32COM or 88SEG x 16COM) with voltage booster
- Infrared Remote Controller with Carrier Generator
- S1C17 High Performance 16-bit RISC CPU Core with C Optimized Compact Code and Serial ICE Support

■ DESCRIPTIONS

The S1C17121 is a 16-bit MCU featuring high-speed low-power operations, compact dimensions, and wide address space. A/D converter and R/F converter are built in and sensor of various analog I/F can be connected. It is suitable for the application of health care product, sports watch and meter module etc. with sensor that is required a small size and micro display in the battery driven.

■ FEATURES

- CPU
Epson original 16-bit RISC CPU core S1C17
16-bit x 16-bit + 32-bit product-sum processor
16 bit ÷ 16bit division arithmetic unit
- IOSC oscillator circuit
2.7 MHz (typ)
Oscillating start up 5 μs (max.)
Boot Clock (External components not required.)
- OSC3 oscillator circuit
Crystal oscillator circuit or ceramic oscillator circuit, 4.2 MHz (max.) or external clock input
- OSC1 oscillator circuit
Crystal oscillator circuit 32.768 kHz (typ)
- Internal ROM
32 Kbytes (for both instructions and data)
- Internal RAM
2 Kbytes
- Internal display RAM
40 bytes
- A/D Converter
10 bit resolution 8ch
- R/F Converter
DC oscillation/AC oscillation/External input 2ch.
- Input/output port
Max. 36-bit general purpose input/output (shared with peripheral circuit input/output pins)
- Serial interface
SPI (master/slave) 1ch.
I²C (master) 1ch.
I²C (slave) 1ch.
UART (230,400bps, IrDA1.0 compatible) 2ch.
Remote controller (REMC) 1ch.
- Timer
8-bit timer (T8F) 2ch.
16-bit timer (T16) 3ch.
PWM timer (T16E) 1ch.
Clock timer (CT) 1ch.
Stopwatch timer (SWT) 1ch.
Watchdog timer (WDT) 1ch.
8-bit OSC1 PWM timer (T8OSC1) 1ch.
- LCD driver
36 SEG x 8 COM or 40 SEG x 4 COM (1/3 bias)
Internal booster power supply circuit (16-value programmable contrast)
- Supply voltage detector
15-value programmable (1.8 V to 3.2 V)
- Interrupt
NMI, P Port Input interrupt 3ch.
Serial Interface interrupt 5ch.
Timer interrupt 9ch.
LCD, SVD, ADC, RFC interrupt
- Power supply voltage
1.8 V to 3.6 V (for normal operations)
- Operating temperatures
-40°C to 85°C (When A/D converter is used -40°C to 50°C)
- Current consumption
SLEEP mode: 0.15 μA typ. (OSC1=OFF, IOSC=OFF, OSC3=OFF)
HALT mode: 0.9 μA typ. (OSC1=32kHz, IOSC=OFF, OSC3=OFF, PCKEN=0x0, LCD OFF)
1.9 μA typ. (OSC1=32kHz, IOSC=OFF, OSC3=OFF, PCKEN=0x0, LCD ON (All LCD On, maximum contrast, VC2 standard))
When operating: 7 μA typ. (OSC1=32kHz, IOSC=OFF, OSC3=OFF, LCD OFF)
250 μA typ. (OSC1=OFF, IOSC=OFF,


S1C17121

OSC3=1MHz ceramic oscillator)

● Shipping form

TQFP14-100 12 mm x 12 mm body, 0.4 mm pitch
VFPGA7H-144 7 mm x 7 mm, body, 0.5 mm pitch
Chip

■ Block Diagram



NOTICE:

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of Economy, Trade and Industry or other approval from another government agency.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©Seiko Epson Corporation 2010, All rights reserved

SEIKO EPSON CORPORATION

SEMICONDUCTOR OPERATIONS DIVISION

■ Epson semiconductor website

http://www.epson.jp/device/semicon_e/

IC Sales Department

IC International Sales Group

421-8 Hino, Hino-shi, Tokyo 191-8501, JAPAN
Phone: +81-42-587-5814 FAX: +81-42-587-5117

Document code: 411826901

First issue Oct, 2009

Revised Feb, 2010 in Japan